

ECO4 Innovation: Approved Innovation Measures

Overview

Under ECO4, once an application for a product to be delivered as an innovation measure is approved, we are required to publish a description of the innovation measure, the date on which it was approved, and whether it is a standard or substantial innovation measure. When a product already deliverable as a standard innovation measure is approved to be delivered as a substantial innovation measure, we are required to publish the approval of that substantial innovation measure, and the date on which its application was approved. This is to allow other obligated suppliers delivering measures which meet any innovation measure description to notify them as an innovation measure; and to allow suppliers and the supply chain to understand what innovation measures have already been approved under the scheme.

All approved innovation measures that can be delivered under ECO4 are listed below, including key characteristics, date of approval, whether a standard or a substantial innovation measure, additional requirements, and any products that can be delivered as that innovation measure. This list includes innovation measures approved under ECO3 and ECO4.

As stated in our ECO4 NMAP Guidance V2.0 (4.11) "Suppliers can apply for products approved as standard IMs to be considered for substantial IM status. For example, ECO3 approved IMs, or ECO4 IMs where additional evidence has been collected to demonstrate a substantial improvement.". Where a previously approved IM with a standard uplift has been approved to accrue a substantial uplift following evaluation and recommendation from the TAP, a new notification number will be created under which IM details will be contained.

When we approve an application for a product already listed under a standard innovation measure to be delivered as a substantial innovation measure, we will create a new innovation measure number and description for that product. Any other products that were listed under the standard innovation measure will remain there unless it is

demonstrated that they also fall within the measure description of the new substantial innovation measure.

It is the responsibility of each supplier to understand the provisions of the Electricity and Gas (Energy Company Obligation) Order 2022 (the ECO4 Order) and how those provisions apply to them. This document is not intended to be a definitive guide to these provisions.

All innovation measures must be installed in accordance with PAS 2030:2023 or MCS standards and PAS 2035:2023 (unless approved as certified by an organisation accredited to ISO/ IEC 17065:2012). Additionally, all innovation measures must be lodged with TrustMark (or an equivalent) and delivered by TrustMark (or an equivalent) registered businesses. Innovation measures must be installed in accordance with Building Regulations and any relevant Agrément certificate listed under "Product(s) meeting description" in the tables below. It is the responsibility of the Retrofit Coordinator overseeing a project and installers, to ensure that innovation measures are installed in accordance with required standards and ECO requirements. Approval of any innovation measure does not constitute confirmation that installation method processes and designs provided are fully compliant with the latest requirements as defined in the relevant PAS and any related guidance.

For each innovation measure, we list what evidence suppliers should hold in order to demonstrate that the correct innovation measure has been installed. Typically, this will be evidence that a particular product was installed or that a particular process was followed. The evidence outlined within V1.17 is in draft form and may be subject to change in future versions of this document.

Additional information on the suitability of a measure for a given property (eg fire safety testing) or restrictions in the applicability of the measure will be communicated to TrustMark (or equivalent body) and may be stated for that innovation measure below. The Retrofit Coordinator and installers delivering innovation measures are responsible for installations and must satisfy themselves that the measure is suitable for a given property prior to installation. We cannot guarantee any claims made in respect of the innovation measures listed below.

Innovation Measure Number: “001”

Innovation measure type

External Wall Insulation (EWI)

Date application approved

20/02/2019

Number for notification

001

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The system involves the installation of a new façade, creating a ventilated cavity between the outer surface of the system and the non-combustible blown fibre insulation.

The product is constructed off-site as a kit of parts. The system is designed and manufactured based on a millimetre accurate 3D model generated from a laser scan of the property to which it is being installed.

Product(s) meeting the description

Soltherm Modulus Brick-ID System (KIWA BDA Agrément BAW-21-223-S-A-UK)

Date product approved under IM: 28/11/2022

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is the Mauer EWI system (KIWA BDA Certificate Number BAW-18-024-S-A-UK) or the Soltherm Modulus Brick-ID System (KIWA BDA Agrément BAW-21-223-S-A-UK).

Evidence type:

1. Photographic evidence mid-install, reflecting new façade and created ventilated cavity.
2. Product/system warranty reflecting ECO household address to which delivered.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "002"

Innovation measure type

Under Floor Insulation (UFI)

Date application approved

22/05/2019

Number for notification

002

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The innovation uses robotics and AI to install underfloor insulation. A robot is inserted into the underfloor void through a small opening in the property. The robot then builds a detailed 3D map of the void space and services. A polyurethane foam is spray applied to the underside of the floor voids, expanding to fill gaps. The robot continuously monitors the thickness of the insulation applied to create a record of each install and to verify installation has been completed correctly.

The installation method reduces disruption for residents and means installation is typically much quicker than traditional methods of under floor insulation.

Product(s) meeting the description

Q-Bot (BBA certificate 17/5440, product sheet 1 - Please note the BBA for this product has been withdrawn. From 28/01/25, there are no products that meet the description.)

Date product approved under IM: 22/05/2019

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The Q-Bot remote installation has been used to install the insulation (BBA certificate 17/5440, product sheet 1)

Evidence type:

1. 3D map created for individual ECO household address to which measure delivered.
2. Install record and verification for individual ECO household address.
3. Product/system warranty reflecting ECO household address to which delivered.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: “003”

Innovation measure type

Smart Thermostat

Date application approved

05/06/2019

Number for notification

003

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The innovation uses GSM connectivity rather than Wi-Fi (which is not universally available), allowing the product to be installed in all households.

The product contains 5 sensors for temperature, motion, light, air pressure and humidity.

The product is a ‘fit and forget’ product from a resident’s perspective. The data collected by the product is compiled with other relevant data to automate and optimise heating settings in a home. The data is also used to provide alerts and KPIs for landlords to support management of the heating needs of their housing stock.

The product includes messaging features allowing landlords to send energy saving tips and advice to residents, schedule appointments, and conduct remote boiler testing.

Product(s) meeting the description

Switchee Smart Thermostats (Gen2 Smart Learning Thermostat and Switchee Econa)

Date product approved under IM: 05/06/2019

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is the 'Switchee Smart Thermostat'.

Evidence type:

1. Photographic evidence of delivery of Switchee Smart Thermostat model(s), Gen2 Smart Learning Thermostat and or Switchee Econa, within an ECO project.
2. Product/system warranty reflecting ECO household address to which delivered.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "004"

Innovation measure type

External Wall Insulation (EWI)

Date application approved

01/11/2019

Number for notification

004

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The system involves the installation of modular, tongue and groove, pre-primed insulation boards that are mechanically fixed to the property using a rail system. The boards are interlocked and finished with one coat of render that is shower proof in 30 minutes, and can be applied in a range of temperatures from -10°C to + 30°C. The system reduces installation time, and downtime due to inclement weather.

Aerogel is used in window detailing for improved thermal performance.

Product(s) meeting the description

Instaclad (BBA certificate 15/5201, product sheet 1)

Please note the BBA certificate for this product has been withdrawn. From 07/11/25 there are no products that meet the description.

Date product approved under IM: 01/11/2019

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is the InstaClad EWI system (BBA certificate 15/5201, product sheet 1).

Evidence type:

1. Photographic evidence mid-install, reflecting rail system installation and the mechanical fixing of modular, tongue and groove, pre-primed insulation boards.
2. Photographic evidence mid-install, reflecting window detailing employing Aerogel.
3. Product/system warranty reflecting ECO household address to which delivered.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "005"

Innovation measure type

Internal Wall Insulation (IWI)

Date application approved

28/11/2019

Number for notification

005

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The system involves the injection of EPS beads with an adhesive into the cavity between the lath and plaster internal lining and the inner face of the exterior wall of traditionally-constructed properties (or where a property has been refurbished, between the internal plasterboard and the inner face of the exterior wall). A cavity width of at least 50mm is required. Injection holes are drilled in a pre-determined pattern, and the EPS beads are coated with the adhesive in the injection gun.

The system reduces the cost and time taken for installation of IWI. Disruption to the householder is also reduced, and there is no impact on the room size.

Product(s) meeting the description

Energystore Superbead (KIWA BDA cert BAW-19-106-S-A-UK)

Date product approved under IM: 28/11/2019

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is Energystore Superbead injected EPS (KIWA BDA cert BAW-19-106-S-A-UK).

The cavity depth has been measured at several points along each wall to obtain an average insulation thickness and the average cavity depth employed for determining the insulation thickness for measure delivery.

Evidence type:

1. Product/system warranty reflecting ECO household address to which delivered.
2. Retainment of measurements of cavity depth, carried out at several points, reflecting the determined average cavity depth for determining insulation thickness for EPS 200.
3. Photographic evidence mid-install of pre-determined drill pattern prior to EPS injection.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "006"

Innovation measure type

Party Cavity Wall Insulation (PWI)

Date application approved

05/02/2020

Number for notification

006

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The system involves the injection of EPS beads with an adhesive into party cavity walls. Injection holes are drilled in a pre-determined pattern in the exterior wall of the property, with no internal drilling required in the loft space. The EPS beads are coated with the adhesive in the injection gun. The drilling technique uses a lance system, with a 360 multidirectional nozzle resulting in a reduced drilling pattern, allowing deployment in a greater range of properties for which the entry points for standard drilling techniques are obstructed by an object on the exterior wall.

There is less disruption to the householder as no internal drilling is required. The speed of installation is reduced by over 50% compared to standard PCWI, and the EPS beads provide greater thermal efficiency over mineral wool.

Product(s) meeting the description

Climabead Party Wall (KIWA BDA cert BAW-18-043-S-A-UK)

Date product approved under IM: 05/02/2020

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is Climabead party cavity wall insulation (KIWA BDA cert BAW-18-043-S-A-UK).

The loft space in all party cavity walls has been filled.

Evidence type:

1. Product/system warranty, including for loft space associated with filled party cavity walls, reflecting ECO household address to which delivered.
2. Photographic evidence mid-install of pre-determined drill pattern in external wall, reflecting the party wall, prior to EPS injection.

Limitations/ Applicability of IM

This measure is only an innovation measure in properties where the cavity extends to the full height of the gable wall. In other properties it is considered a standard party PWI measure

Innovation Measure Number: "007"

Innovation measure type

External Wall Insulation (EWI)

Date application approved

19/02/2020

Number for notification

007

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The EWI system is comprised of mineral wool insulation slabs which are mechanically fixed to the substrate wall with supplementary adhesive. The mechanical fixing goes through two crossed fibreglass mesh strips which are embedded in the base coat adhesive. The Soltherm cross knot is combined with the clamping ring, and stainless steel centre pin fixings. The fibreglass mesh is also used at corners and insulation ends to reinforce insulation fixing. This fixing method enables an increased resistance to wind loads, and reduces delamination.

The system was subjected to extensive testing to demonstrate a lifetime of 75 years.

Product(s) meeting the description

Soltherm 75 (BBA Certificate 16/5319, Product Sheet 4)

Date product approved under IM: 19/02/2020

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is Soltherm 75 (BBA Certificate 16/5319, product sheet 4).

Evidence type:

1. Product/system 75-year manufacturer's warranty reflecting ECO household address to which delivered.
2. Mid-install photographic evidence, reflecting mechanical fixing of mineral wool insulation slabs through two crossed fibreglass mesh strips.
3. Mid-install photographic evidence, reflecting fibreglass mesh employment at corners and insulation ends.

Limitations/ Applicability of IM

The standard 25-year appropriate guarantee will be sufficient for ECO4 eligibility; however, a 75-year manufacturer's warranty must also be provided to the householder to be eligible as an innovation measure.

Innovation Measure Number: “008”

Innovation measure type

Smart Thermostat

Date application approved

24/03/2020

Number for notification

008

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The product is a smart thermostat with an algorithm that automatically reduces the temperature based on the customer’s own requirements, with the aim of setting a more efficient heating schedule. A series of very small adjustments to the scheduled target temperatures are made when the occupant is least likely to notice any drop in temperature. The algorithm runs for a three week period at the start of the heating season, and aims to maintain the more energy efficient heating schedule going forward. Customers are offered the program on their thermostat or phone app and must opt-in to participate. The algorithm learns from any temperature corrections made by the occupant and adjusts the incremental reductions accordingly. Following the implementation of the algorithm, the user retains full ability to overwrite or edit their schedule and set heating points through their thermostat or phone app.

To minimise any risk to households vulnerable to the effects of cold, the algorithm will automatically not be deployed to customers / thermostats where the demand

temperature set by the customer is 18°C or below. The algorithm will also never change the heat setting by more than 1°C.

Product(s) meeting the description

Nest Thermostats with Seasonal Savings algorithm (Nest Learning Thermostat and Thermostat E)

Date product approved under IM: 24/03/2020

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is the Nest Learning Thermostat or Thermostat E.

Evidence type:

1. Photographic evidence of delivery of Nest Thermostats with Seasonal Savings algorithm model(s), Nest Learning Thermostat and or Thermostat E, within an ECO project.
2. Product/system warranty reflecting ECO household address to which delivered.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: “009”

On 16/12/2022 the standard uplift innovation measure IM 009 was approved as a substantial innovation measure. Additional details are available under IM 017. This change followed an application under TAP1 for consideration against the substantial innovation measure criteria.

Innovation Measure Number: "010"

Innovation measure type

Room in Roof Insulation (RIRI)

Date application approved

01/07/2020

Number for notification

010

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

This is a certified room in roof thermal insulation layer envelope and plasterboard lining system, which comprises of a range of flexible and rigid thermal insulation products of various specifications, together with associated fixings, sealant and accessories. The system is for use as a complete thermal insulation envelope of existing room in roof spaces with consideration to the existing buildings ventilation and condensation performance through a pre-design survey.

The thermal roof elements include masonry gable ends, party walls, common walls, dwarf walls, sloping ceilings, flat ceilings above the roof space, dormer window surrounds and residual loft spaces. A water-repellent brick protection treatment is also applied to the outside of masonry gable or common walls. The components used along with a systemised approach provide improved airtightness and thermal performance compared to standard room in roof insulation.

Product(s) meeting the description

MI Systems Design RIRI (BDA Agrément BAR-19-116-S-A-UK)

Date product approved under IM: 01/07/2020

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is the MI Systems Design RIRI (BDA Agrément BAR-19-116-S-A-UK).

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Photographic evidence, reflecting the RIRI completion certificate as being stapled to the loft roof, stating the pre-approval number of the system installation.
3. Documentation reflecting system delivery costings, including the usage of the Stormdry product within the external gable wall of the RIR.
4. Mid-install photographic evidence, reflecting correct sealing of the RIRI system.
5. Post-install photographic evidence, reflecting insulation of the studwork heads.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: “011”

Innovation measure type

External Wall Insulation (EWI)

Date application approved

29/07/2020

Number for notification

011

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The system involves an EWI product for which 50% of installations will be subject to independent technical monitoring using the ECO technical monitoring question set, along with the implementation of a planned inspection and maintenance programme.

The EWI is adhesively and mechanically fixed through reinforcement mesh using high performance anchors, with mesh patches applied over the fixing heads and fully embedded. Stainless steel grade components are used for mechanical fixings, starter track, render stop ends and corner beads. Stainless steel base and corner profiles are also used.

The inspection and maintenance programme is conducted by a suitably qualified third party. The first inspection is conducted within the first 12 months following installation. Subsequent inspections are conducted every five years from the date of the last inspection for a 25 year period. Any maintenance or repairs identified

during these inspections will be rectified at no cost to the end-user, with the exception of wilful / accidental damage and / or vandalism.

These features increase the durability of the product, and quality of installations.

Product(s) meeting the description

Wetherby EWI ("60 years" durability system in BBA certificate 03/4058, product sheet 2 & 3; 09/4625 product sheet 2; and additional Brick Slip system finishes within BBA Certificate 14/5137 product sheet 1&2; Wetherby Heck MW / I-MW render system ETA 18/0229, BBA Assessment Reports S2/63880 & S2/65774)

Date product approved under IM: 29/07/2020 and 11/05/2023 (for additional Brick Slip system finishes within BBA Certificate 14/5137 product sheet 1&2; Wetherby Heck MW / I-MW render system ETA 18/0229, BBA Assessment Reports S2/63880 & S2/65774)

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is the Wetherby EWI ("60 years" durability system in BBA certificate 03/4058, product sheet 2 & 3; 09/4625 product sheet 2; or additional Brick Slip system finishes within BBA Certificate 14/5137 product sheet 1&2; Wetherby Heck MW / I-MW render system ETA 18/0229, BBA Assessment Reports S2/63880 & S2/65774).

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Mid-install photographic evidence, reflecting BBA specified stainless steel anchor fixings being employed and placed through the mesh layer of the system.
3. Mid-install photographic evidence, reflecting BBA specified board fixing sequence for system delivery.

4. Documentation demonstrating at least one carded operative, trained in the specific 60-year lifetime application method, is present on the delivery site for every four operatives.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "012"

Innovation measure type

Boiler

Date application approved

20/11/2020

Number for notification

012

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The product is a domestic sized micro Combined Heat and Power (mCHP) unit that contains a low temperature fuel cell, which extracts hydrogen from natural gas to generate electricity at a lower cost. The waste heat can be used for central heating, or stored in the DHW cylinder contained within the unit. The gas condensing module primarily serves to provide heat during times of peak demand.

The mCHP unit also includes a weather-compensated control unit which can be controlled from the device, or connected to the internet and controlled via a smartphone.

Installations under ECO include a free 10 year service package, which will increase the durability of the product.

These features increase the durability of the product, and quality of installations.

Product(s) meeting the description

Viessmann Vitocalor 300PT2 - E11T/ E19T / E25T / E32T

Date product approved under IM: 20/11/2020

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is the Viessmann Vitocalor 300PT2 - E11T/ E19T / E25T / E32T.

Evidence type: Photographic evidence

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. MCS certification for individual ECO household address to which measure delivered.
3. Documentation reflecting the ECO inclusive, free 10 year service package, has been provided to householders.

Limitations/ Applicability of IM

Installations under ECO, for this measure, include a free 10-year service package.

Delivery is limited to on-gas households, due to natural gas being the fuel type of the measure.

Innovation Measure Number: “013”

Innovation measure type

Solar PV

Date application approved

11/02/2021

Number for notification

013

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The system consists of MCS certified monocrystalline PV modules, with optimiser units built in during the manufacturing process to ensure quality and consistency. The optimised panel offers an increase in electricity production, by allowing generation to continue if part of the string or array is shaded, or develops a fault. Systems can be installed using multiple roof angles and orientations. The addition of the optimiser allows PV installations in properties that may previously have been unsuitable due to shading.

The optimiser results in a reduction of any fire risk from the panels, which will be disconnected if the optimiser identifies a fire, or risk of a fire occurring due to a fault. The system will function without the need for any connection to the internet, however, optional connectivity is available so the occupant or landlord can monitor the system remotely, and receive automatic notifications of any faults that occur (where this optional module is installed after 26/09/23 at no cost to the end-user please see IM022). The system has a 25 year manufacturer’s warranty.

Product(s) meeting the description

UKSOL MCS certified monocrystalline solar PV panels with built in Tigo optimisers.

Date product approved under IM: 11/02/2021

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed (for all installations completed before 07/11/25):

The panels installed are UKSOL Monocrystalline with Tigo optimisers, as visible from the UKSOL/Happy Energy hologram sticker on the inverter.

Evidence type: Photographic evidence

1. Product/system warranty reflecting the ECO household address to which measure was delivered.
2. Documentation reflecting the capacity of solar and the underlying assessment, measured in kWp for ECO household to which delivered.
3. Photographic evidence of product installed in the ECO household.
4. MCS certification for ECO household connected to the solar PV array.

Evidence to held by Suppliers that IM installed (for all installations completed after 07/11/25):

The panels installed are UKSOL with Tigo optimisers, as visible from the model suffix "OPT" and the Tigo logo on the panel labels

Evidence type: Single PDF document containing:

1. The Innovation Measure Verification Certificate (IMVC), showing the address, installer name, number of panels, model number and kWp system size for the ECO household
2. A photo of a UKSOL/Happy Energy hologram sticker on the inverter which contains:

- a. a QR code, which when scanned, allows all PDF evidence to be downloaded
 - b. a tick box to verify that IM013 is being claimed
- 3. Combined UKSOL/Tigo 25 year warranty, reflecting the address to which measure was delivered and showing the MCS installer name and commissioning date
- 4. Photos of the rear of each panel listed in the IMVC, clearly showing the suffix OPT and ideally with an address identifier and panel number e.g. 1 of 8, 2 of 8 etc.
- 5. MCS certification for ECO household showing UKSOL panels were used

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "014"

Innovation measure type

Room in Roof Insulation (RIRI)

Date application approved

11/02/2021

Number for notification

014

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The product is a Room in Roof Insulation (RIRI) system comprised of Aerogel insulants to reduce the thickness of the insulation boards, and pre-fabricated insulated services panel to reduce cold bridging around services.

Aerogel insulation is used for the entirety of the RIRI installation, including the pre-fabricated services panel. The low thermal conductivity of Aerogel significantly reduces the thickness required to achieve the appropriate U-value, and increases the range of properties by enabling installation where space is limited.

The pre-fabricated services panel is an 'insert panel' insulated with Aerogel. It is manufactured off-site for socket boxes and switches, with cables running through a protected conduit. The services panel reduces any thermal bridging behind lighting, power, data & TV sockets, and improves the quality of the installation.

Each installation will be also supported by an individual assessment using WUFI® software, which dynamically predicts moisture movement and storage as well as condensation for each location.

Product(s) meeting the description

Smart Fix Systems RIRI (Aerogel) (BBA certificate 16/5290; ETA-11/0471; EN13162)

Please note the BBA certificate for this product has been withdrawn. As of 28/01/25, there are no products that meet the description.

Date product approved under IM: 11/02/2021

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The RIRI has been insulated with Aerogel and the service panels.

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Mid-install photographic evidence, reflecting delivery of aerogel insulants in combination with insulation boards, and pre-fabricated insulated service panels.
3. Mid-install photographic evidence, reflecting boards butted together with no gaps at abutments.
4. Documentation reflecting the fabrication of the pre-fabricated insulated service panels for individual ECO households.
5. Documentation reflecting individual ECO household assessment of suitability, employing WUFI® software.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "015"

Innovation measure type

External Wall Insulation (EWI)

Date application approved

22/02/2021

Number for notification

015

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The product is an EWI system with adhesively fixed 'Fire Safe Composite' (FSC) panels with supplementary mechanical fixings, both with a reinforced basecoat and render finishes. The system is designed so that the external layers (basecoat, reinforcing mesh, and render) are permanently connected to the substrate through the mesh and adhesive.

The FSC panels are made up of grey EPS boards adhered together with cementitious adhesive and reinforced with an alkali-resistant glass fibre mesh. The FSC panels are marketed at reducing fire spread across the EWI in comparison to standard EPS, PIR and PUR panels, by compartmentalising any fire which does occur. This is intended to lead to improved quality and fire safety in comparison to standard EPS EWI systems.

Please note the system is not certified for use in high rise buildings, and a suitably qualified operative should satisfy themselves of the suitability of the product in regards to fire safety for low rise buildings.

Product(s) meeting the description

Soltherm FSC (Soltherm P EWI system using FSC panels (BBA certificate 18/5557, product sheet 3)

Date product approved under IM: 22/02/2021

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is the Soltherm P EWI system using FSC panels, as described in BBA certificate 18/5557, product sheet 3.

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Mid-install photographic evidence, reflecting delivery of FSC panels, grey EPS boards adhered together with cementitious adhesive and reinforced with an alkali-resistant glass fibre mesh, as specified within BBA certification.

Limitations/ Applicability of IM

The system is not certified for use in high rise buildings, and a suitably qualified operative should satisfy themselves of the suitability of the product in regard to fire safety for low rise buildings.

Innovation Measure Number: "016"

Innovation measure type

Smart Thermostat

Date application approved

24/01/2022

Number for notification

016

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

N/A (ECO3-approved IM)

Characteristics of innovation measure

The product is a smart thermostat with a programmable thermostatic display interface and an app, which can be used via two connectivity modes, WI-FI and Bluetooth Low Energy (BLE). The system detects the communication modes available and automatically connects to the most suitable, without requiring any manual input from the user, thereby enabling the householder to continue to set and change heating schedules and operate heating controls if one connectivity mode drops.

The programmable interface has an unreplaceable battery with a twelve-year manufacturer's warranty, therefore in a similar manner to wired smart thermostats, battery changes are not required throughout the lifetime of the device.

To minimise risks related to system or battery failures, the programmable thermostatic display can be overridden, allowing householders to continue to operate their heating system in a basic on/off manner.

Product(s) meeting the description

Secure Meters C1727 Smart Thermostat

Date product approved under IM: 24/01/2022

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is the Secure Meters Smart Thermostat model C1727.

Evidence type:

1. Photographic evidence of delivery of Secure Meters Smart Thermostat model C1727, within an ECO project.
2. Product/system warranty reflecting ECO household address to which delivered.
3. Evidence suitable handover has been carried out with household(s), ensuring they can connect to the Secure Meters Smart Thermostat app via Wi-Fi. This could be demonstrated as part of a handover checklist.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "017"

Innovation measure type

Cavity Wall Insulation (CWI)

Date application approved

16/12/2022

Number for notification

017

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

EDF Energy

Characteristics of innovation measure

The system involves the injection of mineral wool insulation into cavity walls in properties over 5 storeys using a rope access installation technique. The insulation is comprised of granulated glass mineral wool fibres, treated with an inert water repellent during manufacture. The rope access installation technique is an alternative to the use of scaffolding, and involves the use of ropes and associated equipment to gain access to and from the required work position on the external wall of the building, and be supported there. The rope access technicians are members of IRATA, and box testing is used to ensure the pressure is correct for adequate fill of each storey. The installation technique has been adapted to enable mineral wool CWI to be installed.

The rope access technique reduces the installation time and costs associated with installing CWI in high rise properties, as scaffolding is not required. The use of mineral wool insulation meets the fire safety regulations for buildings over 18m

high, in line with Building Regulations 2010, Fire Safety Approved Document B, 2019 edition.

Product(s) meeting the description

ARP CWI (BBA certificate 89/2294, product sheet 2. KIWA BDA Certificate Number BAW-17-071-S-A-UK)

Date product approved under IM: 16/12/2022

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

Suppliers to evidence the CWI mineral wool product has been delivered by rope access.

Evidence type: Photographic evidence of delivery, CWI mineral wool product invoices from project delivery

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Photographic evidence of rope access being employed for CWI delivery.
3. Document retention, reflecting building height for which this measure has been delivered.

Limitations/ Applicability of IM

Delivery of measure as an innovation measure only where building block is above 4 stories high.

This measure was previously approved under ECO3 for a 25% uplift. If this measure is installed under ECO4 before the 16/12/2022 it should be notified as IM 009 and will receive a 25% uplift, with no supplier uplift award.

Innovation Measure Number: “018”

Innovation measure type

Solar PV

Date application approved

21/12/2022

Number for notification

018

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

E.ON

Characteristics of innovation measure

The system connects up to 15 flats with single-phase output connections, with each flat allocated a set proportion of the system’s total generated electricity. Each flat is connected behind the meter. The system allocates electricity to individual flats according to real time consumption, up to each flats’ allocation, by way of the system housing multiple switches (one per connection), that are controlled by onboard software, that monitors individual energy demand for each flat. Solar energy delivery and optimisation is automated. Householders are able to export excess solar energy.

The system guarantees that there is no possibility of the crossflow of energy between connections behind-the-meter, and it does not allow for faults to transfer between connections behind-the-meter. The system meets grid interconnection standards for the United Kingdom and solar PV systems are MCS certifiable.

The system comes with a 10 year parts and labour warranty. The measure is provided with 10 years fault monitoring at no cost, with any faults associated with the system under correct installation repaired at no cost to the system owner or households connected. Data packages can be offered to the system owner at either a cost or at no cost, and are optional.

Product(s) meeting the description

Allume Energy's SolShare, model number SOLSHARE-3P-XX-YY¹

Date product approved under IM: 21/12/2022

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

Allume Energy's Solshare system, model SOLSHARE-3P-XX-YY has been installed.

Each flat connected to the system has an MCS certificate that details the exact capacity of solar, measured in kWp, that is attributed to it.

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Documentation reflecting the exact capacity of solar and the underlying assessment, measured in kWp, for each individual flat connected to the system.
3. Photographic evidence of product installed in flat blocks.
4. MCS certification for each household connected to the shared solar PV array.

¹ Notation XX-YY refers to the watt capacity for the Solar PV model(s) specified.



Making a positive difference
for energy consumers

Limitations/ Applicability of IM

To qualify for the innovation measure uplift, the system must connect two or more households.

Innovation Measure Number: “019”

Innovation measure type

Cavity Wall Insulation (CWI)

Date application approved

10/03/2023

Number for notification

019

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

ScottishPower

Characteristics of innovation measure

The system involves the injection of EPS beads with a water-based adhesive, which may be used in masonry cavity walls where there is a minimum 40mm cavity width, or in party walls. The product is injected through external masonry walls, employing a bespoke drill pattern consisting of a series of 22mm injection holes.

The approved CWI system uses EPS beads produced in a supply chain using independently verified biofuels which supports a reduction in lifetime emissions for the product.

Product(s) meeting the description

EnergyStore Superbead 33+ CWI System (KIWA BDA Agrément BAW-22-255-S-A-UK)

Date product approved under IM: 10/03/2023

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is the EnergyStore Superbead 33+ CWI System (KIWA BDA Agrément BAW-22-255-S-A-UK)

Evidence type:

1. Product/system warranty reflecting the ECO household address to which it is delivered.
2. Photographic evidence mid-install of pre-determined drill pattern prior to EPS injection.
3. Evidence that EPS beads produced in a supply chain using independently verified biofuels have been used, and relevant certification confirming their production using biofuels.

Limitations/ Applicability of IM

The measure would not be suitable for delivery where the cavity width is below 40mm.

Innovation Measure Number: “020”

Innovation measure type

Solar PV

Date application approved

25/05/2023

Number for notification

020

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

E.ON

Characteristics of innovation measure

The system consists of MCS certified Solar PV modules with integrated power optimisers together with an inverter to provide increased power output. The system enables installation where shading, and or multiple roof angles and orientations may be present, increasing the range of properties to-which solar PV may be delivered. The system has an automatic safety shutdown (Safe DC) with AFCI (Arc Fault Circuit Interrupter) and heat detection at the module level, reducing the risk of damage caused by fire or system faults.

Additional app connectivity features enable users to have a virtual layout of the system to aid fault detection and remediation, and remote system monitoring. Automatic notifications will be sent to users when a system fault is detected.

These features increase output, durability, and safety.

Product(s) meeting the description

MCS certified SolarEdge Smart Module with integrated S series (sense connect) Power Optimizers.

Date product approved under IM: For model number SPVXXX-R60DBMG (MCS BAPT8787-101-XXXW) - 25/05/2023. For model number SPVXXX-R54PDTL (MCS BAPT8886-112-XXXW) – 20/12/2023, where XXX refers to module wattage. For all other MCS certified SolarEdge Smart Modules with integrated S series (sense connect) Power Optimizers – 12/04/2024.

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed (for all installations completed before 14/01/26):

The product installed is the MCS certified SolarEdge Smart Module with integrated S series (sense connect) Power Optimizers.

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Documentation reflecting the capacity of solar and the underlying assessment, measured in kWp for ECO household to which delivered.
3. Photographic evidence of product installed in ECO household.
4. MCS certification for ECO household connected to the solar PV array.
5. A data plan has been provided to households without Wi-Fi at no cost to the end-user for a minimum of 12 years.
6. The Solar PV system is set up by installers employing the free to use MySolarEdge App.
7. Photographic evidence of the combined SolarEdge, CCL Components, and LMF Energy Services coded sticker affixed to the SolarEdge inverter on the

linked portal, in order to verify the relevant approved product has been installed at the particular property.

8. A warranty has been registered for the Solar PV array, including system components, covering over at least a 25-year period.

Evidence to be held by Suppliers that IM installed (for all installations completed on or after 14/01/26):

The product installed is the MCS certified SolarEdge Smart Module with integrated S series (sense connect) Power Optimizers.

Evidence type:

1. Documentation reflecting the capacity of solar and the underlying assessment, measured in kWp for ECO household to which delivered.
2. Photographic evidence of product installed in ECO household.
3. MCS certification for ECO household connected to the solar PV array.
4. A data plan has been provided to households without Wi-Fi at no cost to the end-user for a minimum of 12 years.
5. The Solar PV system is set up by installers employing the free to use MySolarEdge App, demonstrated by a screenshot from the SolarEdge monitoring website which shows the "logical layout" page, with serial numbers for the inverter and all optimisers, with the address shown in a black box by hovering the mouse over the address extract
6. Photographic evidence of the SolarEdge coded sticker affixed to the SolarEdge inverter, registered on the LMF Energy Services portal, in order to verify the relevant approved product has been installed at the particular property.
7. A warranty has been registered for the Solar PV array, including system components, covering over at least a 25-year period.

Limitations/ Applicability of IM

The installer should ensure Wi-Fi is present at the household, providing a data plan where required, to ensure the benefits of the free to use MySolarEdge App can be accessed by householders.

Innovation Measure Number: “021”

Innovation measure type

External Wall Insulation (EWI)

Date application approved

11/05/2023

Number for notification

021

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

E.ON

Characteristics of innovation measure

The system involves an EWI product for which 50% of installations will be subject to technical monitoring, along with the implementation of a planned inspection and maintenance programme.

The EWI is adhesively and mechanically fixed through reinforcement mesh using high performance stainless steel pinned anchors, with mesh patches applied over the fixing heads and fully embedded.

A robust and regular inspection and maintenance programme will be employed, whereby inspections are undertaken by the manufacturer annually for 5 years after installation. A third party will conduct inspections within the first 12 months following installation. Subsequent inspections by the third party are conducted every five years from the date of the last inspection for a 25 year period. Any maintenance or repairs identified during these inspections will be rectified at no cost to the end-user, with the exception of wilful / accidental damage and / or vandalism.

These features increase the durability of the product, and quality of installations.

Product(s) meeting the description

InstaClad Robust EWI ("60 years" durability system in BBA certificate 12/4944, product sheet 2)

Please note the BBA certificate for this product has been withdrawn. From 07/11/25 there are no products that meet the description.

Date product approved under IM: 11/05/2023

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is InstaClad Robust EWI ("60 years" durability system in BBA certificate 12/4944, product sheet 2)

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Mid-install photographic evidence, reflecting BBA specified stainless steel anchor fixings being employed and placed through the mesh layer of the system.
3. Mid-install photographic evidence, reflecting BBA specified board fixing sequence for system delivery.
4. Documentation demonstrating at least one carded operative, trained in the specific 60-year lifetime application method, is present on the delivery site for every four operatives.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: “022”

Innovation measure type

Solar PV

Date application approved

26/09/2023

Number for notification

022

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

EDF Energy

Characteristics of innovation measure

The system consists of MCS certified monocrystalline PV modules, with optimiser units factory fitted during the manufacturer’s assembly process, to ensure quality and consistency. The optimised panel offers an increase in electricity production, by allowing generation to continue if part of the string or array is shaded, or develops a fault. Systems can be installed using multiple roof angles and orientations. The addition of the optimiser allows PV installations in properties that may previously have been unsuitable due to shading.

The optimiser puts the panel into protection mode when it identifies a short circuit fault. The PV Off feature disconnects the DC power at the panel level in the event of a power cut, or when AC power is switched off in the home, decreasing the risk of DC electrocution. Connectivity of the system via the Cloud Connect unit provides occupant(s) or landlord(s) with remote system monitoring. Notifications will be sent to users when a system fault is detected. The system has a 25-year manufacturer’s warranty.

These features increase output, durability, and safety.

Product(s) meeting the description

UKSOL MCS certified monocrystalline solar PV panels with built in Tigo optimisers and CCA/TAP modules specified.

Date product approved under IM: 26/09/2023

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed (for all installations completed before 07/11/25):

The product installed is UKSOL Monocrystalline with Tigo optimisers, as visible from the UKSOL/Happy Energy hologram sticker on the inverter, which contains a QR code, which will link to a dedicated web page showing the installation photos and verifying that the panels on the roof are UKSOL Tigo optimised.

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Documentation reflecting the capacity of solar and the underlying assessment, measured in kWp for ECO household to which delivered.
3. Photographic evidence of product installed in ECO household.
4. MCS certification for ECO household connected to the solar PV array.
5. A data plan has been provided to households without Wi-Fi at no cost to the end-user for a minimum of 10 years.
6. A manufacturer warranty has been registered for the Solar PV array, covering at least a 25-year period.
7. The additional CCA/TAP modules included at no cost to the end-user.
8. A label is placed on the CCA module warning householders to not disconnect the system.

9. A PDF guide is included within the handover notes for the system, to ensure householder understand how to register and employ the Tigo app.

Evidence to be held by Suppliers that IM installed (for all installations completed after 07/11/25):

The panels installed are UKSOL with Tigo optimisers, as visible from the model suffix "OPT" and the Tigo logo on the panel labels.

Evidence type: Single PDF document containing:

1. The Innovation Measure Verification Certificate (IMVC), showing the address, installer name, number of panels, model number and kWp system size for the ECO household
2. A photo of a UKSOL/Happy Energy hologram sticker at the home which contains:
 - a. a QR code, which when scanned, allows all PDF evidence to be downloaded
 - b. a tick box to verify that IM022 is being claimed
 - c. a tick box confirming if customer internet or a 10 year data dongle was used
 - d. a warning message to the household not to disconnect the system
3. Combined UKSOL/Tigo 25 year warranty, reflecting the address to which measure was delivered and showing the MCS installer name and commissioning date
4. Photos of the rear of each panel listed in the IMVC, clearly showing the suffix OPT and ideally with an address identifier and panel number e.g. 1 of 8, 2 of 8 etc.
5. MCS certification for ECO household showing UKSOL panels were used

6. Photo of Tigo CCA in electrical enclosure, included at no cost to the end-user
7. A photo of a data sim and modem provided to households where they have no internet, at no cost to the end-user, with evidence of 10 years' pre-paid data
8. Tigo monitoring screenshot, displaying a matching number of panels and the address
9. A copy of a PDF guide with property address, provided to the householder at handover, explaining how they can connect to the Tigo monitoring app

Limitations/ Applicability of IM

The installer should ensure Wi-Fi is present at the household, providing a data plan where required, to ensure the benefits of the Cloud Connect unit can be accessed by householders.

Innovation Measure Number: "023"

Innovation measure type

External Wall Insulation (EWI)

Date application approved

28/09/2023

Number for notification

023

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

ScottishPower

Characteristics of innovation measure

The EWI comprises mineral wool slabs which are mechanically fixed to the substrate. The mechanical fixing goes through a layer of basecoat which contains a mesh reinforcement. A second layer of basecoat with further reinforcement mesh is then applied over the fixings. The system can be installed on steel, masonry or timber substrates.

The system design enables an increased impact and wind load resistance, as well as improved fire performance.

Product(s) meeting the description

Soltherm Dynamic EWI (KIWA BDA Agrément BAE-21-215-S-A-UK and BAW-22-253-S-A-UK)

Date product approved under IM: 28/09/2023

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is the Soltherm Dynamic EWI system (KIWA BDA Certificate Number BAE-21-215-S-A-UK or BAW-22-253-S-A-UK)

Evidence type:

1. Product/system warranty reflecting ECO household address to which it is delivered.
2. Mid-install photographic evidence, reflecting delivery of Soltherm Dynamic as specified by product BDA.
3. That site visits have been undertaken by Soltherm, with all non-conformances being addressed.
4. Orders have been checked to ensure the correct materials have been ordered in line with the specification.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: “024”

Innovation measure type

External Wall Insulation (EWI)

Date application approved

30/11/2023

Number for notification

024

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

EDF Energy

Characteristics of innovation measure

The system involves an EWI product for which all installations will be subject to technical monitoring including pre-installation checks, along with the implementation of a planned inspection and maintenance programme and easy to access digital records of installation, inspections and warranty.

The EWI is adhesively and mechanically fixed, with a double layer of reinforcement mesh being applied to increase the mechanical strength of the system. Each phase of installation will be photographed by installers and assessed by technical operative before the next phase of installation can begin. High performance fixings will be used for all enabling works to increase the quality of installation, and reduce chance of water ingress to the system.

A robust and regular inspection and maintenance programme will be employed, whereby inspections are undertaken by the manufacturer within the first 12 months after installation and subsequent inspections are conducted every five years from the date of the last inspection for a 60 year period. Any maintenance

or repairs identified during these inspections will be rectified at no cost to the end-user, with the exception of wilful / accidental damage and / or vandalism.

Digital records of the installation, warranty, and maintenance regime will be kept on a website accessible to the end-user via a QR code attached to the outside of the property.

These features increase the durability of the product, and quality of installations.

Product(s) meeting the description

DuraShield Pro EWI (BBA certificate 18/5503, product sheet 2 and BBA certificate 18/5503, product sheet 1)

Date product approved under IM: BBA certificate 18/5503, product sheet 2: 30/11/2023. BBA certificate 18/5503, product sheet 1: 19/02/2024

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is DuraShield Pro EWI (BBA certificate 18/5503, product sheet 2 or product sheet 1)

Evidence type:

1. Product/system warranty for full 60-year lifetime (25-year TrustMark approved IBG plus 35-year manufacturer warranty) reflecting ECO household address to which measure delivered.
2. Mid-install photographic evidence, reflecting SWIFIX fixings being used for enabling works.
3. Evidence that the QA has been carried out through the app or website, and that each installation phase has been approved before the next phase has begun.
4. Evidence that the QR code has been fitted to the external wall of the property to which the system is delivered. The QR code must be linked to a



Making a positive difference
for energy consumers

website which stores digital records of the installations, warranty, and maintenance plan for the end-user.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: “025”

Innovation measure type

Solar PV

Date application approved

10/02/2024

Number for notification

025

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

Octopus Energy Ltd.

Characteristics of innovation measure

The system consists of MCS certified monocrystalline PV modules, with optimiser units factory fitted during the manufacturer’s assembly process, to help quality and consistency. The optimised panel offers an increase in electricity production, by allowing generation to continue if part of the string or array is shaded, or develops a fault. Systems can be installed using multiple roof angles and orientations. The addition of the optimiser allows PV installations in properties that may previously have been unsuitable due to shading.

The optimiser puts the panel into protection mode when it identifies a short circuit fault. The PV Off feature disconnects the DC power at the panel level in the event of a power cut, or when AC power is switched off in the home, decreasing the risk of DC electrocution. Connectivity of the system via the Cloud Connect unit provides the user with remote system monitoring. Notifications will be sent to users when a system fault is detected. The system has a 25-year manufacturer’s warranty.

Product(s) meeting the description

Anglo Solar PV MCS certified monocrystalline solar panels with built in Tigo optimisers and CCA/TAP modules specified.

Date product approved under IM: 19/02/2024

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed (for all installations completed before 03/09/25)

The product installed is Anglo Solar PV with Tigo optimisers, as visible from the Anglo Solar/Retrofit Practice silver hologram sticker on the electrical enclosure containing the Tigo CCA, which contains a QR code, which will link to a dedicated web page showing the installation photos and verifying that the panels on the roof are Anglo Solar Tigo optimised.

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Documentation reflecting the capacity of solar and the underlying assessment, measured in kWp for ECO household to which delivered.
3. Photographic evidence of product installed in ECO household.
4. MCS certification for ECO household connected to the solar PV array.
5. A data plan has been provided to households without Wi-Fi at no cost to the end-user for a minimum of 10 years.
6. A manufacturer warranty has been registered for the Solar PV array, covering over at least a 25-year period.
7. The additional CCA/TAP modules included at no cost to the end-user.
8. A label is placed on the CCA module warning householders to not disconnect the system.

9. A guide is included within the handover notes for the system, to ensure householder understand how to register and employ the Tigo app.

Evidence to be held by Suppliers that IM installed (for all installations completed after 03/09/25)

The panels installed are Anglo Solar with Tigo optimisers, as visible from the model suffix "TIG" and the Tigo logo on the panel labels.

Evidence type - a single PDF document containing:

1. The Innovation Measure Verification Certificate (IMVC), showing the address, installer name, number of panels, model number and kWp system size for the ECO household
2. A photo of an Anglo/Retrofit Practice hologram sticker at the home which contains:
 - a. a QR code, which when scanned, allows all PDF evidence to be downloaded
 - b. a tick box to verify that IM025 is being claimed
 - c. a tick box confirming if customer internet or a 10 year data dongle was used
 - d. a warning message to the household not to disconnect the system
3. Combined Anglo/Tigo 25 year warranty, reflecting the address to which measure was delivered and showing the MCS installer name and commissioning date
4. Photos of the rear of each panel listed in the IMVC, clearly showing the suffix TIG and ideally with an address identifier and panel number e.g. 1 of 8, 2 of 8 etc.
5. MCS certification for ECO household showing Anglo panels were used
6. Photo of Tigo CCA in electrical enclosure, included at no cost to the end-user

7. A photo of a data sim and modem provided to households where they have no internet, at no cost to the end-user, with evidence of 10 years' pre-paid data
8. Tigo monitoring screenshot, displaying a matching number of panels and the address
9. A copy of a PDF guide with property address, provided to the householder at handover, explaining how they can connect to the Tigo monitoring app

Limitations/ Applicability of IM

The installer should ensure Wi-Fi is present at the household, providing a data plan where required, to ensure the benefits of the Cloud Connect unit can be accessed by householders.

Innovation Measure Number: “026”

On 24 October 2024 the standard uplift innovation measure IM 026 was approved as a substantial innovation measure. Additional details are available under IM 031. This change followed an application under TAP10 for consideration against the substantial innovation measure criteria.

Innovation Measure Number: "027"

Innovation measure type

External Wall Insulation (EWI)

Date application approved

03/05/2024

Number for notification

027

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

E.ON

Characteristics of innovation measure

The system involves an EWI product installed following a 60-year durability methodology and with a planned inspection and maintenance programme.

The EWI is adhesively and mechanically fixed through reinforcement mesh using stainless steel pinned anchors. Stainless steel components are used for mechanical fixings, render stop ends and corner beads. Stainless steel base, edge and corner profiles are also used.

A robust and regular inspection and maintenance programme will be employed, whereby the manufacturer will conduct an inspection after 12 months following installation. Subsequent inspections are conducted every five years from the date of the last inspection. Any maintenance or repairs identified during these inspections will be rectified at no cost to the end-user, with the exception of damage caused by vandalism, movement caused by structural instability and general neglect of the main building.

These features increase the durability of the product, and quality of installations.

Product(s) meeting the description

JUB 60 Year EWI ("60 years" durability system in BBA certificate 12/4955, product sheet 1)

Date product approved under IM: 03/05/2023

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is JUB 60 Year EWI ("60 years" durability system in BBA certificate 12/4955, product sheet 1)

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Mid-install photographic evidence, reflecting BBA specified stainless steel anchor fixings being employed and placed through the mesh layer of the system.
3. Mid-install photographic evidence, reflecting BBA specified board fixing sequence for system delivery.
4. Documentation demonstrating at least one operative in each application team has been trained in the application method by the certificate holder.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "028"

Innovation measure type

Boiler

Date application approved

14/05/2024

Number for notification

028

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

EDF Energy

Characteristics of innovation measure

The system includes an MCS certified air-to-water ASHP using R290 refrigerant which comes with an extended 10-year parts and labour warranty, 10 years of data, and access to 10 years of remote monitoring support from the manufacturer at no cost to the end-user.

An additional remote commissioning check is carried out by the manufacturer to ensure that the system has been set up appropriately by the installing engineer.

These features are designed to improve durability of the system and reduce the disruption to the end-user.

Product(s) meeting the description

Trianco Activair High Temp ASHP – MCS: BSI KM 785261 and MCS HP0289/03

Date product approved under IM: 14/05/2024 and 02/10/2024 for MCS HP0289/03.

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is a Trianco Activair High Temp ASHP – MCS: BSI KM 785261 or MCS HP0289/03

Evidence type:

1. A manufacturer Certificate of Commissioning and Innovation Measure approval has been uploaded as part of the ECO claim, showing the address, model number, confirmation of the manufacturer's commissioning check and provision of 10 year parts and labour warranty.
2. Photographic evidence that a hologram adhesive label with a QR code on the heat pump outdoor unit, which when scanned goes to a website where a copy of the above certificate can be downloaded for verification.
3. Photographic evidence of product installed in ECO household, including evidence that an adhesive label is prominently positioned on the outdoor unit and DHW cylinder, making clear that free remote monitoring support and a parts and labour warranty are included for 10-years.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: “029”

Innovation measure type

Solar PV

Date application approved

29/05/2024

Number for notification

029

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

E.ON

Characteristics of innovation measure

The system consists of MCS certified monocrystalline PV modules, with optimiser units. The optimised panel offers an increase in electricity production, by allowing generation to continue if part of the string or array is shaded or develops a fault. Systems can be installed using multiple roof angles and orientations. The addition of the optimiser allows PV installations in properties that may previously have been unsuitable due to shading.

Connectivity of the system via the Cloud Connect unit provides occupant(s) or landlord(s) with remote system monitoring. Notifications will be sent to users when a system fault is detected.

Product(s) meeting the description

InstaGen Solar PV MCS certified monocrystalline solar panels with Tigo optimisers and CCA/TAP modules specified.

Date product approved under IM: 29/05/2024

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is InstaGen Solar PV with Tigo optimisers and CCA/TAP modules.

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Documentation reflecting the capacity of solar and the underlying assessment, measured in kWp for ECO household to which delivered.
3. Pre, mid and post installation photographs of the product installed in the ECO household, all photographs to include the optimiser with panels.
4. MCS certification for ECO household connected to the solar PV array.
5. A data plan has been provided to households without Wi-Fi at no cost to the end-user for a minimum of 10 years.
6. A manufacturer warranty has been registered for the Solar PV array, covering at least a 12-year period and a 30-year linear power output warranty.
7. The additional CCA/TAP modules are included at no cost to the end-user, demonstrated through photographic evidence.
8. A label is placed on all devices which clearly describes the free services available to the end-user and how to utilise these services.
9. A guide is included within the handover notes for the system, to ensure householder can connect to and use the monitoring system provided by the CCA.

Limitations/ Applicability of IM

The installer should ensure Wi-Fi is present at the household, providing a data plan where required, to ensure the benefits of the Cloud Connect unit can be accessed by householders.

Innovation Measure Number: “030”

Innovation measure type

External Wall Insulation (EWI)

Date application approved

12/07/2024

Number for notification

030

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

E.ON

Characteristics of innovation measure

The system involves an EWI product for which all installations incorporate a cementitious basecoat and adhesive which is produced using cement replacement technologies.

This production methodology supports a reduction in embodied carbon of the EWI system.

Product(s) meeting the description

K Systems EWI when specified with K Systems HP14 ECO for basecoat and adhesive layers (BBA certificate 18/5570, product sheets 1,2,3,4,5,6,7,8,9)

Date product approved under IM: 12/07/2024

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is K Systems EWI when specified with K Systems HP14 ECO for basecoat and adhesive layers (BBA certificate 18/5570, product sheets 1,2,3,4,5,6,7,8,9)

Evidence type:

1. The issued system design specifies the use of 'K Systems HP14 ECO' and is in accordance with the requirements within BBA certificate 18/5570.
2. Purchase orders from installers and invoices for the specific K Systems HP14 ECO product.
3. Proportional on-site inspection reports by K Systems Application Specialists, including photographic evidence of the materials & product batch number observed on-site and being installed. Product batch numbers are traceable within Kilwaughter Minerals quality system.
4. Warranty issue information and certificates, including explicit identification of the addresses covered by the warranty and with specific reference to the use of K Systems HP14 ECO.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "031"

Innovation measure type

Boiler

Date application approved

24/10/2024

Number for notification

031

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

Octopus Energy Ltd.

Characteristics of innovation measure

The product is an MCS certified air-to-water ASHP which comes with an additional Appliance Function Check (AFC) from the manufacturer to ensure the system has been installed to the required standard. The AFC is free to the end-user.

The product comes with a 12-year manufacturer Annual Servicing (AS) and maintenance package and a 12-year warranty at no cost to the end-user, helping ensure the product operates as intended.

Product(s) meeting the description

Vaillant aroTHERM Plus ASHP 3.5kW / 5kW / 7kW / 10kW / 12kW (MCS KIWA 00016/021HP / 00016/018HP / 00016/019HP / 00016/022HP / 00016/020HP)

Date product approved under IM: 01/03/2024 as a standard innovation measure.
24/10/2024 as a substantial innovation measure.

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is Vaillant aroTHERM Plus ASHP 3.5kW / 5kW / 7kW / 10kW / 12kW (MCS KIWA 00016/021HP / 00016/018HP / 00016/019HP / 00016/022HP / 00016/020HP) together with a 12-year AFC & AS Package – Part number 87000000731

Evidence type:

1. Documentation that a Vaillant engineer has completed an Appliance Function Check of the product and a warranty has been registered for the ASHP covering a 12-year period.
2. Documentation reflecting the model employed in ECO household to which it is delivered.
3. Photographic evidence of product installed in ECO household, including evidence that a sticker is prominently positioned on the DHW cylinder making clear that free servicing and maintenance is included for 12-years.
4. Provision of a letter to the ECO household, with date and address, outlining the extended guarantee and indicating that a service agreement is in place, providing servicing each year for 11 years, beginning 12 months after the installation date. The letter must also detail that a minimum of four attempts will be made to contact the end-user to book servicing annually.

Limitations/ Applicability of IM

This measure was previously approved for a 25% uplift. If this measure is installed with a DOCI before the 24/10/2024 it should be notified as IM 026 and will receive a 25% uplift.

Innovation Measure Number: “032”

Innovation measure type

Solar PV

Date application approved

24/10/2024

Number for notification

032

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

Octopus Energy Ltd.

Characteristics of innovation measure

The system consists of MCS certified monocrystalline PV modules, with optimiser units built in during the manufacturing process to ensure quality and consistency. The optimised panel offers an increase in electricity production, by allowing generation to continue if part of the string or array is shaded, or develops a fault. Systems can be installed using multiple roof angles and orientations. The addition of the optimiser allows PV installations in properties that may previously have been unsuitable due to shading.

The optimiser results in a reduction of any fire risk from the panels, which will be disconnected if the optimiser identifies a fire, or risk of a fire occurring due to a fault. The system will function without the need for any connection to the internet.

The system has a 25 year manufacturer’s warranty.

Product(s) meeting the description

Anglo Solar PV MCS certified monocrystalline solar panels with built in Tigo optimisers.

Date product approved under IM: 24/10/2024

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed (for all installations completed before 03/09/25)

The product installed is Anglo Solar PV with Tigo optimisers, as visible from the Anglo Solar/Retrofit Practice silver hologram sticker on the system inverter, which contains a QR code, which will link to a dedicated web page showing the installation photos and verifying that the panels on the roof are Anglo Solar Tigo optimised.

Evidence type: Photographic evidence

1. Product/system warranty reflecting the ECO household address to which the measure was delivered.
2. Documentation reflecting the capacity and the underlying assessment, measured in kWp for ECO household to which delivered.
3. Photographic evidence of the product installed in the ECO household, including that the measure has an adhesive label from the manufacturer authenticating the measure and Tigo Optimisers.
4. MCS certification for ECO household connected to the solar PV array.

Evidence to be held by Suppliers that IM installed (for all installations completed after 03/09/25)

The panels installed are Anglo Solar with Tigo optimisers, as visible from the model suffix "TIG" and the Tigo logo on the panel labels

Evidence type – a single PDF document containing:

1. The Innovation Measure Verification Certificate (IMVC), showing the address, installer name, number of panels, model number and kWp system size for the ECO household
2. A photo of an Anglo/Retrofit Practice hologram sticker on the inverter, which contains:
 - a. a QR code, which when scanned, allows all PDF evidence to be downloaded
 - b. a tick box to verify that IM032 is being claimed
3. Combined Anglo/Tigo 25 year warranty, reflecting the address to which measure was delivered and showing the MCS installer name and commissioning date
4. Photos of the rear of each panel listed in the IMVC, clearly showing the suffix TIG and ideally with an address identifier and panel number e.g. 1 of 8, 2 of 8 etc.
5. MCS certification for ECO household showing Anglo Solar panels were used

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "033"

Innovation measure type

Boiler

Date application approved

20/12/2024

Number for notification

033

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

E.ON

Characteristics of innovation measure

The system includes an MCS certified air-to-water ASHP which comes with a 10-year warranty and 10-years of data which enables access to "Active Care". This monitoring software is intended to identify and remediate issues remotely to reduce the necessity for on-site interventions. A tutoring service is provided to the end-user to provide reports intended to help them understand how to use their ASHP effectively.

These features are designed to improve the durability of the system and reduce the disruption to the end user.

Product(s) meeting the description

Ariston Thermo Nimbus Pocket 35/50/80/80T/120/120T/150/150T M NET R32 (MCS certification ICIM-PDC 000111/ ICIM-PDC-000117/ ICIM-PDC-000108), Nimbus Plus 35 M NET R32 35/50/80/80T/120/120T/150/150T (MCS certification ICIM-PDC 000111/ ICIM-PDC-000117/ ICIM-PDC-000108), Nimbus Compact-UK 35/50/80/80T/120/120T/150/150T M NET R32 (ICIM-PDC-000109, ICIM-PDC-

000115, ICIM-PDC-000106), Nimbus Plus 35/50/80/80T/120/120T/150/150T S NET R32 (ICIM-PDC-000114, ICIM-PDC-000120, ICIM-PDC-000176-01, ICIM-PDC-000176-03, ICIM-PDC-000176-02)

Date product approved under IM: 18/12/2024

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The products installed are Ariston Thermo Nimbus Pocket 35/50/80/80T/120/120T/150/150T M NET R32 (MCS certification ICIM-PDC 000111/ ICIM-PDC-000117/ ICIM-PDC-000108), Nimbus Plus 35 M NET R32 35/50/80/80T/120/120T/150/150T (MCS certification ICIM-PDC 000111/ ICIM-PDC-000117/ ICIM-PDC-000108), Nimbus Compact-UK 35/50/80/80T/120/120T/150/150T M NET R32 (ICIM-PDC-000109, ICIM-PDC-000115, ICIM-PDC-000106), Nimbus Plus 35/50/80/80T/120/120T/150/150T S NET R32 (ICIM-PDC-000114, ICIM-PDC-000120, ICIM-PDC-000176-01, ICIM-PDC-000176-03, ICIM-PDC-000176-02)

Evidence type:

1. Photographic evidence of product installed in an ECO household, including evidence that the product sticker is prominently positioned on the outdoor unit, which includes reminder to installer that product registration is mandatory for 10-year warranty activation.
2. A Certificate of confirmation that the product has been registered on the Ariston Product Registration Portal and the 10-year warranty has been activated.

3. Screenshots of Ariston NET Pro portal, which shows free live remote monitoring support and Active Care diagnostic functions on the 'Hub' have been set up.
4. Photographic evidence which shows GPRS 10-year data sim unit installed alongside heat pump, providing internet connection in all installations, ensuring remote functionality is available for at least the length of the 10-year warranty.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "034"

Innovation measure type

Smart Thermostat

Date application approved

14/01/2025

Number for notification

034

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

ScottishPower

Characteristics of innovation measure

The measure is a smart thermostat designed to be used exclusively with heat pumps. The measure uses internal temperature data to determine the heat loss of the home, and weather data to adjust the heat pump flow temperature in order to heat the home more efficiently. This automatic functionality reduces reliance on the end-user to adjust their system settings and is designed to increase the speed at which the system suits the schedule of the end-user.

These features are designed to increase the efficiency of the heat pump and reduce end-user heating costs.

Product(s) meeting the description

Homely Smart Thermostat Version 3.0

Date product approved under IM: 14/01/2025

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is Homely Smart Thermostat Version 3.0

Evidence type:

1. Photographic evidence of the product installed in an ECO household, including evidence that the product had an adhesive label attached which details the product functionality and manufacturer contact details.
2. Screenshots from the installer app which confirm a successful installation at the specific ECO household.
3. Evidence of confirmation from the manufacturer to the sponsoring supplier that the measure has been installed successfully, including detailing the address to which the measure has been installed.
4. Evidence that the project the measure is installed on also includes the installation of a heat pump.

Limitations/ Applicability of IM

The measure must only be installed where the homeowner already has a Wi-Fi connection.

The measure must only be installed in a project which also includes the installation of a heat pump.

Innovation Measure Number: "035"

Innovation measure type

Loft Insulation (LI)

Date application approved

13/03/2025

Number for notification

035

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

ScottishPower

Characteristics of innovation measure

The system involves a loft insulation material manufactured in the UK from UK grown industrial hemp and recycled jute. The use of these materials supports a reduction in embodied carbon of the loft insulation measure.

Product(s) meeting the description

IndiBreathe Flex Insulation (BBA certificate 24/7266, product sheet 2)

Date product approved under IM: 13/03/2025

Suppliers are required to retain the following evidence to demonstrate that this IM has been installed:

Evidence to be held by Suppliers that IM installed

The product installed is IndiBreathe Flex Insulation (BBA certificate 24/7266, product sheet 2)

Evidence type:

1. Product/system warranty reflecting ECO household address to which it is delivered.
2. Mid-install photographic evidence, reflecting delivery of IndiBreathe Flex as specified by product BBA.
3. Photographic evidence of the warning label attached within the insulated space.
4. A copy of the IAA's ISA form including digital images of appropriate fire breaks and non-combustible insulation material being installed.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: “036”

Innovation measure type

Solar PV

Date application approved

01/04/2025

Number for notification

036

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

E.ON

Characteristics of innovation measure

The system consists of MCS certified monocrystalline PV modules, with optimiser units. The optimised panel offers an increase in electricity production, by allowing generation to continue if part of the string or array is shaded, or develops a fault. Systems can be installed using multiple roof angles and orientations. The addition of the optimiser allows PV installations in properties that may previously have been unsuitable due to shading.

The optimiser puts the panel into protection mode when it identifies a short circuit fault. The PV Off feature disconnects the DC power at the panel level in the event of a power cut, or when AC power is switched off in the home, decreasing the risk of DC electrocution. Connectivity of the system via the Cloud Connect unit provides occupant(s) or landlord(s) with remote system monitoring. Notifications will be sent to users when a system fault is detected. The system has a 25-year manufacturer’s warranty.

These features increase output, durability, and safety.

Product(s) meeting the description

InstaGen Solar PV MCS certified monocrystalline solar panels with Tigo optimisers and CCA/TAP modules specified.

Date product approved under IM: 01/04/2025

Suppliers are required to retain evidence that demonstrates this IM has been installed, such as:

Evidence to be held by Suppliers that IM installed

The product installed is InstaGen Solar PV with Tigo optimisers and CCA/TAP modules.

Evidence type:

1. Product/system warranty reflecting ECO household address to which measure delivered.
2. Documentation reflecting the capacity of solar and the underlying assessment, measured in kWp for ECO household to which delivered.
3. Pre, mid and post installation photographs of the product installed in the ECO household, all photographs to include the optimiser with panels.
4. MCS certification for ECO household connected to the solar PV array.
5. A data plan has been provided to households without Wi-Fi at no cost to the homeowner for a minimum of 10 years.
6. A manufacturer warranty has been registered for the Solar PV array, covering at least a 25-year period. The warranty must make clear that the entire system is warrantied, including connections between individual components, and provide clear contact details for the end-user to contact if necessary.
7. The additional CCA/TAP modules are included at no cost to the end-user, demonstrated through photographic evidence including the hologram sticker.

8. A label is placed on all devices which clearly describes the free services available to the end-user and how to utilise these services.
9. A guide is included within the handover notes for the system, to ensure householder can connect to and use the monitoring system provided by the CCA.
10. Screenshot of the Tigo energy monitoring portal, showing CCA/TAP set up has been completed, including green rectangles signifying the successful installation of the optimiser.
11. Screenshot of registration on the InstaGen portal, demonstrating that optimisers and panels are installed, connected to the internet and CCA/TAP device is setup and configured.

Limitations/ Applicability of IM

The installer should ensure Wi-Fi is present at the household, providing a data plan where required, to ensure the benefits of the Cloud Connect unit can be accessed by householders.

Innovation Measure Number: "037"

Innovation measure type

Boiler

Date application approved

16/05/2025

Number for notification

037

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

E.ON

Characteristics of innovation measure

The product is an MCS certified air-to-water ASHP which comes with 12-year annual servicing and maintenance package and 12-year warranty at no cost to the end-user. The ASHP also comes with 12 years of remote monitoring.

These features are designed to improve durability, increase comfort and reduce disruption to the end user.

Product(s) meeting the description

Grant Aeron3 / HPID6R32 / HPID10R32 / HPID13R32 / HPID17R32 (MCS No. BBA 0009/15/16/17/18)

Grant Aeron3 HPR2904 / HPR29065 / HPR2909 / HPR29012 / (MCS HP0265 01/02/03/04/05)

Date product approved under IM: 16/05/2025

Suppliers are required to retain evidence that demonstrates this IM has been installed, such as:

Evidence to be held by Suppliers that IM installed

The product installed is Grant Aerona3 / HPID6R32 / HPID10R32 / HPID13R32 / HPID17R32 (MCS No. BBA 0009/15/16/17/18) or Grant Aerona HPR2904 / HPR29065 / HPR2909 / HPR29012 / HPR290155 (MCS HP0265 01/02/03/04/05) with remote monitoring and 12 year annual servicing and maintenance package and warranty plan.

Evidence type:

1. Documentation that a Grant engineer has completed an Appliance Set-Up of the product and a warranty has been registered for the ASHP covering a 12-year period.
2. Documentation reflecting the model employed in ECO household to which it is delivered.
3. Photographic evidence of product installed in ECO household, including evidence that a sticker is prominently positioned on the DHW cylinder making clear that free remote monitoring and free servicing and maintenance is included for 12-years.
4. Provision of a letter to the ECO household, with date and address, outlining the extended guarantee and indicating that a service agreement is in place, providing servicing each year for 11 years, beginning 12 months after the installation date. The letter must also detail that a minimum of four attempts will be made to contact the end-user to book servicing annually, including a letter being sent to the householder.

Limitations/ Applicability of IM

None.

Innovation Measure Number: "038"

Innovation measure type

Boiler

Date application approved

16/05/2025

Number for notification

038

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

EDF Energy

Characteristics of innovation measure

The system includes an MCS certified air-to-water ASHP using R290 refrigerant which comes with an extended 10-year parts and labour warranty, 10 years of data, and access to 10 years of remote monitoring support from the manufacturer at no cost to the end-user. Additionally, the measure comes with a 10-year annual service plan at no cost to the end-user.

An additional remote commissioning check is carried out by the manufacturer to ensure that the system has been set up appropriately by the installing engineer.

These features are designed to improve durability of the system and reduce the disruption to the end-user.

Product(s) meeting the description

Trianco Activair High Temp ASHP – MCS: BSI KM 785261 and MCS HP0289/03

Date product approved under IM: 16/05/2025

Suppliers are required to retain evidence that demonstrates this IM has been installed, such as:

Evidence to be held by Suppliers that IM installed

The product installed is a Trianco Activair High Temp ASHP – MCS: BSI KM 785261 and MCS HP0289/03

Evidence type:

1. A manufacturer Certificate of Commissioning and Innovation Measure approval has been uploaded as part of the ECO claim, showing the address, model number, confirmation of the manufacturer's commissioning check and provision of 10 year parts and labour warranty, and the 10-year service plan has been selected.
2. Provision of a letter to the ECO household, with date and address, outlining the extended guarantee and indicating that a service agreement is in place, providing servicing each year for 9 years, beginning 12 months after the installation date. The letter must also detail that attempts will be made to contact the end-user to book servicing annually, via email, Warmlink app, in-room display, and via post.
3. Photographic evidence that a hologram adhesive label with a QR code on the heat pump outdoor unit, which when scanned goes to a website where a copy of the above certificate can be downloaded for verification.
4. Photographic evidence of product installed in ECO household, including evidence that an adhesive label is prominently positioned on the outdoor unit and DHW cylinder, making clear that free remote monitoring support, parts and labour warranty, and servicing are included for 10-years.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "039"

Innovation measure type

Boiler

Date application approved

16/05/2025

Number for notification

039

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

British Gas

Characteristics of innovation measure

The system includes an MCS certified air-to-water ASHP using R290 refrigerant which comes with an extended 10-year parts and labour warranty, 10 years of data, and access to 10 years of remote monitoring support from the manufacturer at no cost to the end-user. Additionally, the measure comes with a 10-year biennial service plan at no cost to the end-user.

The measure comes with a performance guarantee to ensure remediation where performance drops below 340% efficiency.

The measure includes a centralised control unit to adjust performance based on weather forecasts and household heating patterns.

An additional remote commissioning check is carried out by the manufacturer to ensure that the system has been set up appropriately by the installing engineer.

These features are designed to improve durability of the system and reduce the disruption to the end-user.

Product(s) meeting the description

Aira ASHP – MCS HP0372

Date product approved under IM: 16/05/2025

Suppliers are required to retain evidence that demonstrates this IM has been installed, such as:

Evidence to be held by Suppliers that IM installed

The product installed is an Aira ASHP – MCS HP0372

Evidence type:

1. A copy of the handover letter provided at installation, with date and address, outlining the 10-year warranty, servicing provision, free remote monitoring, and comfort guarantee. The letter must also detail that the attempts made to contact the end-user to book servicing annually via phone/email/SMS, post, and in person.
2. Photographic evidence of the adhesive label with a QR code on the heat pump outdoor unit and indoor cylinder, which when scanned goes to a website with details on the warranty and terms. The sticker indicates that a service will be scheduled within 12 months of occupancy change.
3. A copy of the manufacturers certificate of commissioning and IM approval, confirming the installation address, model number, completion of the manufacturer commissioning check, and provision of the 10-year all-inclusive package.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "040"

Innovation measure type

Boiler

Date application approved

06/06/2025

Number for notification

040

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

EDF Energy

Characteristics of innovation measure

The product is an MCS certified air-to-water ASHP which comes with installation and commissioning check by the manufacturer's engineer to ensure the system has been installed to the required standard.

The product comes with 6 annual services and a 7-year warranty at no cost to the end-user, which will help ensure the product operates as designed.

Product(s) meeting the description

Ideal Logic Air 7 year 4kW AH750664 / 5kW AH750665 / 8kW AH750666 / 10kW AH750667 / (MCS: KIWA 00027/024 HP / KIWA 00027/023 HP / KIWA 00027/021 HP / KIWA 00027/022 HP)

Date product approved under IM: 06/06/2025

Suppliers are required to retain evidence that demonstrates this IM has been installed, such as:

Evidence to be held by Suppliers that IM installed

The product installed is Ideal Logic Air 7 year 4kW AH750664 / 5kW AH750665 / 8kW AH750666 / 10kW AH750667 / (MCS: KIWA 00027/024 HP / KIWA 00027/023 HP / KIWA 00027/021 HP / KIWA 00027/022 HP)

Evidence type:

1. Documentation that an Ideal engineer has completed an installation and commissioning check and a warranty has been registered for the ASHP covering a 7-year period.
2. Documentation reflecting the model employed in ECO household to which it is delivered.
3. Photographic evidence of product installed in ECO household, including evidence that a sticker is prominently positioned on the DHW cylinder making clear that free servicing and maintenance is included for 7-years.
4. Provision of a letter to the ECO household, with date and address, outlining the extended guarantee and indicating that a service agreement is in place, providing servicing each year for 6 years, beginning 12 months after the installation date. The letter must also detail that a minimum of four attempts will be made to contact the end-user to book servicing annually.

Limitations/ Applicability of IM

None.

Innovation Measure Number: "041"

Innovation measure type

Boiler

Date application approved

09/07/2025

Number for notification

041

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

EDF Energy

Characteristics of innovation measure

The product is an MCS certified air-to-water ASHP which comes with installation and commissioning check by the manufacturer's engineer to ensure the system has been installed to the required standard, 10 years of remote monitoring support from the manufacturer at no cost to the end-user and 10 years of data.

The product comes with 9 annual services and a 10-year warranty at no cost to the end-user, which will help ensure the product operates as designed.

Product(s) meeting the description

Ideal Logic Air 10-year 4kW AH750664 / 5kW AH750665 / 8kW AH750666 / 10kW AH750667 / (MCS: KIWA 00027/024 HP / KIWA 00027/023 HP / KIWA 00027/021 HP / KIWA 00027/022 HP)

Date product approved under IM: 09/07/2025

Suppliers are required to retain evidence that demonstrates this IM has been installed, such as:

Evidence to be held by Suppliers that IM installed

The product installed is Ideal Logic Air 10-year 4kW AH750664 / 5kW AH750665 / 8kW AH750666 / 10kW AH750667 / (MCS: KIWA 00027/024 HP / KIWA 00027/023 HP / KIWA 00027/021 HP / KIWA 00027/022 HP)

Evidence type:

1. Documentation that an Ideal engineer has completed an installation and commissioning check and a warranty has been registered for the ASHP covering a 10-year period.
2. Documentation reflecting the model employed in ECO household to which it is delivered.
3. Photographic evidence of product installed in ECO household, including evidence that a sticker is prominently positioned on the heat pump indoor control box making clear that free servicing and maintenance, a warranty and remote monitoring is included for 10-years. Photographic evidence must also clearly show that the remote monitoring component has been installed.
4. A screenshot of the remote monitoring system which shows it is functioning, the specific unit installed and the address of the installation.
5. Provision of a letter to the ECO household, with date and address, outlining the extended guarantee and indicating that a service agreement is in place, providing servicing each year for 9 years, beginning 12 months after the installation date. The letter must also detail that a minimum of four attempts will be made to contact the end-user to book servicing annually.

Limitations/ Applicability of IM

None.

Innovation Measure Number: "042"

Innovation measure type

Boiler

Date application approved

27/08/2025

Number for notification

042

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

Octopus Energy.

Characteristics of innovation measure

The product is an MCS certified air-to-water ASHP which comes with 10-year warranty at no cost to the end-user. The ASHP also comes with 12 years of remote monitoring, data for the lifetime of the product and pre-installation commissioning check.

These features are designed to improve durability, increase comfort and reduce disruption to the end user.

Product(s) meeting the description

Global Energy Systems - Castletown 6.6kW (MCS HP0010/08), Rothesay 9.9kW – (MCS HP0010/09), Cartmel 11.2kW (MCS HP0010/10)

Date product approved under IM: 27/08/2025

Suppliers are required to retain evidence that demonstrates this IM has been installed, such as:

Evidence to be held by Suppliers that IM installed

The product installed is Global Energy Systems Castletown 6.6kW (MCS HP0010/08), Rothesay 9.9kW (MCS HP0010/09), or Cartmel 11.2kW (MCS HP0010/10) which comes with 10-year warranty, 12 years of remote monitoring and data for the lifetime of the product.

Evidence type:

1. A copy of the handover letter provided at installation, with date and address, outlining the 10-year warranty, 12 year free remote monitoring and data for the lifetime of the product.
2. Photographic evidence that a hologram adhesive label with a QR code on the heat pump outdoor unit, which when scanned goes to a website where a copy of the warranty can be downloaded for verification.
3. A copy of the manufacturers certificate of commissioning and IM approval, confirming the installation address, model number and completion of the manufacturer commissioning check

Limitations/ Applicability of IM

None.

Innovation Measure Number: "043"

Innovation measure type

Boiler

Date application approved

28/11/2025

Number for notification

043

Innovation measure type/uplift

Standard innovation measure/25%

Awarded supplier uplift

Octopus Energy.

Characteristics of innovation measure

The product is an MCS certified air-to-water ASHP which comes with 10-year warranty at no cost to the end-user. The ASHP also comes with remote monitoring for the lifetime of the system, a 10-year data plan and a manufacturer remote commissioning check.

These features are designed to improve durability, increase comfort and reduce disruption to the end user.

Product(s) meeting the description

Cosy 6 (MCS HP0255/03)

Cosy 9 (MCS HP0255/04)

Date product approved under IM: 28/11/2025

Suppliers are required to retain evidence that demonstrates this IM has been installed, such as:

Evidence to be held by Suppliers that IM installed

The product installed is Cosy 6 (MCS HP0255/03) or Cosy 9 (MCS HP0255/04) which comes with 10-year warranty, lifetime remote monitoring and a 10-year data plan.

Evidence type:

1. A copy of the handover letter provided at installation, with date and address, outlining the 10-year warranty, free remote monitoring and 10-year data plan.
2. Photographic evidence that an adhesive label with a QR code is affixed to the heat pump outdoor unit and internal hub. When scanned, this enables the end user to easily download the Octopus app to register the ASHP as well as access hot water and heating guidance and settings.
3. A copy of the manufacturer's certificate of commissioning and IM approval, confirming the installation address, model number and completion of the manufacturer commissioning check.

Limitations/ Applicability of IM

None.

Innovation Measure Number: "044"

Innovation measure type

Boiler

Date application approved

19/12/2025

Number for notification

044

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

E.ON

Characteristics of innovation measure

The system includes an MCS certified air-to-water ASHP which comes with a 10-year warranty and 10-years of data which enables access to "Active Care". This monitoring software is intended to identify and remediate issues remotely to reduce the necessity for on-site interventions. A tutoring service is provided to the end-user to provide reports intended to help them understand how to use their ASHP effectively.

The system also comes with a 10-year annual service plan at no cost to the end-user.

These features are designed to improve the durability of the system and reduce the disruption to the end user.

Product(s) meeting the description

Ariston Thermo Nimbus Pocket 35/50/80/80T/120/120T/150/150T M NET R32
(MCS certification ICIM-PDC 000111/ ICIM-PDC-000117/ ICIM-PDC-000108),

Nimbus Plus 35 M NET R32 35/50/80/80T/120/120T/150/150T (*MCS certification ICIM-PDC 000111/ ICIM-PDC-000117/ ICIM-PDC-000108*), Nimbus Compact-UK 35/50/80/80T/120/120T/150/150T M NET R32 (*ICIM-PDC-000109, ICIM-PDC-000115, ICIM-PDC-000106*), Nimbus Plus 35/50/80/80T/120/120T/150/150T S NET R32 (*ICIM-PDC-000114, ICIM-PDC-000120, ICIM-PDC-000176-01, ICIM-PDC-000176-03, ICIM-PDC-000176-02*)

Date product approved under IM: 19/12/2025

Suppliers are required to retain evidence that demonstrates this IM has been installed, such as:

Evidence to be held by Suppliers that IM installed

The products installed are Ariston Thermo Nimbus Pocket 35/50/80/80T/120/120T/150/150T M NET R32 (*MCS certification ICIM-PDC 000111/ ICIM-PDC-000117/ ICIM-PDC-000108*), Nimbus Plus 35 M NET R32 35/50/80/80T/120/120T/150/150T (*MCS certification ICIM-PDC 000111/ ICIM-PDC-000117/ ICIM-PDC-000108*), Nimbus Compact-UK 35/50/80/80T/120/120T/150/150T M NET R32 (*ICIM-PDC-000109, ICIM-PDC-000115, ICIM-PDC-000106*), Nimbus Plus 35/50/80/80T/120/120T/150/150T S NET R32 (*ICIM-PDC-000114, ICIM-PDC-000120, ICIM-PDC-000176-01, ICIM-PDC-000176-03, ICIM-PDC-000176-02*)

Evidence type:

1. Photographic evidence of product installed in an ECO household, including evidence that the product sticker is prominently positioned on the outdoor unit, which includes reminder to installer that product registration is mandatory for 10-year warranty activation and 10-year annual service.
2. A Certificate of confirmation that the product has been registered on the Ariston Product Registration Portal and the 10-year warranty and 10-year annual service has been activated.

3. Screenshots of Ariston NET Pro Portal which shows free live remote monitoring support and Active Care diagnostic functions on the 'Hub' have been set up.
4. A Certificate of confirmation that all installations have been provided with 10 years of data, providing internet connection in all installations, ensuring remote functionality is available for at least the length of the 10-year warranty.

Limitations/ Applicability of IM

None specified

Innovation Measure Number: "045"

Innovation measure type

Solar PV

Date application approved

09/01/2026

Number for notification

045

Innovation measure type/uplift

Substantial innovation measure/45%

Awarded supplier uplift

E.ON

Characteristics of innovation measure

The system consists of MCS-certified monocrystalline PV modules, with optimiser units. The optimised panel offers an increase in electricity production, by allowing generation to continue if part of the string or array is shaded, or develops a fault. Systems can be installed using multiple roof angles and orientations. The addition of the optimiser allows PV installations in properties that may previously have been unsuitable due to shading.

The optimiser puts the panel into protection mode when it identifies a short circuit fault. The PV Off feature disconnects the DC power at the panel level in the event of a power cut, or when AC power is switched off in the home, decreasing the risk of DC electrocution. Connectivity of the system via the Gateway module, which is provided at no cost to the end user, provides occupant(s) or landlord(s) with remote system monitoring. Notifications will be sent to users when a system fault is detected. The system has a 25-year manufacturer's warranty.

These features increase output, durability, and safety.

Product(s) meeting the description

JA Solar PV MCS-certified monocrystalline solar panels from the JAM 54/48 DXX panel range with Archai iOPT 800W Smart Optimisers and Gateway modules.

Date product approved under IM: 09/01/2026

Suppliers are required to retain evidence that demonstrates this IM has been installed, such as:

Evidence to be held by Suppliers that IM installed

The product installed is JA Solar PV panels from the JAM 54/48 DXX panel range with Archai iOPT 800W Smart Optimisers and Gateway modules.

Evidence type:

1. Documentation reflecting the capacity of solar and the underlying assessment, measured in kWp for the ECO household to which it is delivered.
2. Photographic evidence showing the internal gateway module is affixed with a QR coded sticker which when scanned gives the product serial number and information on how to submit warranty claims.
3. Pre-installation photos of the panel serial number, barcode, and JA Solar logo.
4. Pre-installation photos of the optimiser fitted to each panel, including the serial number and QR code.
5. Post-installation photographs of the product installed in the ECO household.
6. Screenshot of the Archai Installer Portal, showing the system view from the Station Details Layout tab, and Station Details. This should include the system's installation address, and evidence of system monitoring updates to demonstrate that the Gateway unit is setup and configured.
7. For installations located within 500 metres of the sea, confirmation from JA Solar and Archai that the Combined Warranty Package is valid at the stated

coastal location. Otherwise, a screenshot from Google Earth showing the address is not within 500m of the sea.

8. A 25-year system warranty has been produced and linked to the ECO household, with the above evidence being verified by the manufacturer. The warranty provides clear contact details for the end-user to contact when they have a claim, and the warranty clearly states that the entire system is covered.
9. MCS certification for ECO households connected to the solar PV array.
10. Documentation showing that a data plan has been provided to households without Wi-Fi at no cost to the homeowner for a minimum of 10 years.
11. Evidence that a guide is included within the handover notes for the system, to ensure householders can connect to and use the monitoring system provided by the Gateway.

Limitations/ Applicability of IM

The installer should ensure Wi-Fi is present at the household, providing a data plan where required, to ensure the benefits of the Gateway unit can be accessed by householders.